

Carlisle Spray Foam Insulation Safety Data Sheet

1. Identification of Substance:

Product Name: SEALTITE PRO CLOSED CELL REGULAR

Supplier Identification: Carlisle Spray Foam Insulation

Address: 100 Enterprise Dr. Cartersville, GA 30120 **Telephone:** (770) 607-0755

24-Hr. Emergency Phone Number: CHEMTREC (800) 424-9300 INTERNATIONAL: +1-(703) 527-3887

Product Use: Polyurethane polyol component

2. Hazards Identification:

GHS Ratings:

| Skin corrosive | 2 | Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation |
|----------------------------------|----|--|
| Eye corrosive | 2A | Eye irritant: Subcategory 2A, Reversible in 21 days |
| Skin sensitizer | 1 | Skin sensitizer |
| Reproductive toxin | 1B | Presumed, Based on experimental animals |
| Organ toxin repeated exposure | 2 | Presumed to be harmful to human health- Animal studies with significant toxic effects relevant to humans at generally moderate exposure (guidance)- Human evidence in exceptional cases |

GHS Hazards

| H315 H317 H319 H360 H373 GHS Precautions | Causes skin irritation May cause an allergic skin reaction Causes serious eye irritation May damage fertility or the unborn child May cause damage to organs through prolonged or repeated exposure |
|---|---|
| | |
| P201 | Obtain special instructions before use |
| P202 | Do not handle until all safety precautions have been read and understood |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray |
| P264 | Wash hands thoroughly after handling |
| P272 | Contaminated work clothing should not be allowed out of the workplace |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection |
| P281 | Use personal protective equipment as required |
| P314 | Get Medical advice/attention if you feel unwell |
| P321 | Specific treatment is urgent (see Section 4 First Aid measures) |
| P362 | Take off contaminated clothing and wash before reuse |
| P363 | Wash contaminated clothing before reuse |
| P302+P352 | IF ON SKIN: Wash with soap and water |

| P305+P351+P338 | IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing |
|----------------|---|
| P308+P313 | IF exposed or concerned: Get medical advice/attention |
| P332+P313 | If skin irritation occurs: Get medical advice/attention |
| P333+P313 | If skin irritation or a rash occurs: Get medical advice/attention |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P405 | Store locked up |
| P501 | Dispose of contents/container in accordance with existing federal, state, and local environmental control laws. |

Signal Word: Danger



Acute Toxicity: Eyes: Corrosive to eyes. Skin: Irritating to skin. Inhalation: Not expected to be a route of exposure. Ingestion: Harmful if swallowed. Consult physician.

Chronic Effects: Possible harmful target organ effects

| Chemical Name | CAS number | Weight Concentration % |
|--|------------|------------------------|
| 2-Propanol, 1-chloro-, phosphate (3:1) | 13674-84-5 | 5.00% - 10.00% |
| Diethylene glycol | 111-46-6 | 5.00% - 10.00% |
| 1,1,1,3,3-Pentafluoropropane | 460-73-1 | 5.00% - 10.00% |
| Triethanolamine | 102-71-6 | 1.00% - 5.00% |
| 2-Butoxyethanol | 111-76-2 | 1.00% - 5.00% |
| Glycerin | 56-81-5 | 1.00% - 5.00% |
| 2-Propanol, 1-[bis[3-(dimethylamino)propyl]amino]- | 67151-63-7 | 1.00% - 5.00% |

4. First Aid Measures:

Inhalation: If inhaled and symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

After Eye Contact: Rinse opened eye for at least 15 minutes under running water. Remove contact lenses if present and easy to do so, and continue rinsing. If irritation persists contact physician

After Skin Contact: Clean affected area with soap and plenty of water.

Notes to Physician: Treat symptomatically.

5. Fire Fighting Measures:

 Flash Point:
 143 C (289 F)

 LEL: N/A
 UEL: N/A

 Upper and Lower Explosive Limits listed if known.
 Suitable Extinguishing Agents: Water spray, CO2, Foam, Dry chemical.

Information about Protection against Explosions and Fires: Keep away from flames and sources of heat. Closed containers may rupture when exposed to extreme heat.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, oxides of phosphorus, hydrocarbons, traces of HCN, hydrogen chloride gas, hydrogen fluoride.

Protective Equipment: Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

6. Accidental Release Measures:

Person-Related Safety Precautions: Use appropriate personal protective equipment during clean up. Evacuate and keep unnecessary people out of spill area. Avoid contact with skin and eyes.

Measures for Environmental Protection: Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.

Small Spills: Absorb with earth, sand or other absorbent material and transfer to containers for later disposal. Wipe up with absorbent material (e g. cloth, fleece) clean surface thoroughly to remove residual contamination.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use an absorbent material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

7. Handling and Storage:

Information for Safe Handling: Avoid contact with eyes, skin, or inhalation.

Storage Requirements: Store in dry, well ventilated area. Keep containers tightly closed. Store between 50°F-80°F. Material may settle.

Regulatory Requirements: Obey all local, state, and federal requirements.

| 8. Exposure Controls and Personal Protection: | | | | |
|---|---|-----------------------|-----------------------------------|--|
| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits | |
| 2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5 | Not Established | Not Established | Not Established | |
| Diethylene glycol 111-46-6 | Not Established Not Established | | Not Established | |
| 1,1,1,3,3-Pentafluoropropane 460-73-1 | Not Established | Not Established | Not Established | |
| Triethanolamine 102-71-6 | Not Established | 5 mg/m3 TWA | Not Established | |
| 2-Butoxyethanol 111-76-2 | 50 ppm TWA; 240 mg/m3 TWA | 20 ppm TWA | NIOSH: 5 ppm TWA; 24 mg/m3 TWA | |
| Glycerin 56-81-5 | 15 mg/m3 TWA (mist, total particulate); 5 mg/m3 TWA (mist, respirable fraction) | | Not Established | |
| 2-Propanol, 1-[bis[3-(dimethylamino)propy I]amino]- 67151-63-7 | Not Established | Not Established | Not Established | |

Engineering Controls: No specific measures required if proper PPE precautions are followed.

General Protective and Hygienic Measures: Usual precautionary measures should be adhered to when handling chemicals.

Respiratory Protection: In spray applications, an organic vapor/particulate respirator or air supplied unit is necessary.

Protection of Hands: Protective chemical resistant gloves.

Eye Protection: Chemical resistant goggles must be worn.

Body Protection: Protective work clothing. Launder separately.

Contaminated Gear: Observe local requirements. Dispose of in accordance with local/state/federal regulations.

9. Physical and Chemical Properties:

Physical properties listed where known.

| Appearance: Amber liquid | Odor: Amine odor | |
|---------------------------------|---|--|
| Vapor Pressure: N/A | Odor threshold: N/A | |
| Vapor Density: N/A | pH: N/A | |
| Specific Gravity 1.15 | Melting point: N/A | |
| Freezing point: N/A | Solubility: N/A | |
| Boiling range: 100 - 342°C | Flash point: 289°F,143°C | |
| Evaporation rate: N/A | Flammability: N/A | |
| Explosive Limits: N/A | Partition coefficient N/A (n-octanol/water): | |
| Autoignition temperature: 229°C | Decomposition temperature: N/A | |

10. Stability and Reactivity:

Chemical Incompatible Materials: Avoid contact with isocyanates and strong oxidizing agents.

Hazardous Polymerization: Not expected to occur.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, oxides of phosphorus, hydrocarbons, traces of HCN, hydrogen chloride gas, hydrogen fluoride

<u>11. Toxicological Information:</u>

Mixture Toxicity Oral Toxicity LD50: 3,130mg/kg Inhalation Toxicity LC50: 20mg/L Component Toxicity

Individual Toxicity Values Listed if Known

Acute Toxicity: Eyes: Corrosive to eyes. Skin: Irritating to skin. Inhalation: Not expected to be a route of exposure. Ingestion: Harmful if swallowed. Consult physician.

Chronic Effects: Possible harmful target organ effects.

Routes of Entry: Ingestion, skin contact, eye contact. Target Organs: Skin, eyes, reproductive system, kidneys Chemicals with Known or Possible Carcinogenic Effects:

| None | | | None | |
|-----------------------------|--|--|------|--|
| 12. Ecological Information: | | | | |

General Information: Based on experience, no adverse effects are to be expected if correct disposal procedures have been followed as indicated in section 13.

Individual component ecotoxicity listed if known.

Component Ecotoxicity

| 2-Propanol, 1-chloro-, phosphate (3:1) | 96 Hr LC50 Brachydanio rerio: 56.2 mg/L [static]; 96 Hr LC50 Pimephales promelas: 98 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30 mg/L [static] 48 Hr EC50 Daphnia magna: 63 mg/L 72 Hr EC50 Desmodesmus subspicatus: 45 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 4 mg/L |
|---|--|
| Diethylene glycol | 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 84000 mg/L |

| Triethanolamine | 96 Hr LC50 Pimephales promelas: 10600 - 13000 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: >1000 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 450 - 1000 mg/L [static] 72 Hr EC50 Desmodesmus subspicatus: 216 mg/L; 96 Hr EC50 Desmodesmus subspicatus: 169 mg/L |
|-----------------|---|
| 2-Butoxyethanol | 96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 2950 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L |
| Glycerin | 96 Hr LC50 Oncorhynchus mykiss: 51 - 57 mL/L [static] |

13. Disposal Considerations:

Recommendation: Observe local requirements. Dispose of in accordance with local/state/federal environmental control laws.

Empty Container Precautions: Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. Do not reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed and container is empty prior to disposal. Contact the Reusable Industrial Packaging Association (RIPA) at 301-577-3786 to find a drum re-conditioner in North America (www.reusablepackaging.org).

14. Transport Information:

DOT Regulated Components:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods unless specifically cited below:

| Agency | Proper Shipping Name | <u>UN Number</u> | Packing Group | Hazard Class |
|--------|----------------------|------------------|---------------|--------------|
| | None | | | |

15. Regulatory Information:

OSHA HAZARD COMMUNICATION STANDARD: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA 311/312 Hazard Categories: Acute health hazard, chronic health hazard.

WARNING: This product can expose you to chemicals listed below, which are known to the State of California to cause cancer, birth defects, or reproductive harm. For more information, visit www.P65Warnings.ca.gov

1,4-Dioxane 123-91-1 51 PPM CARC Ethylene glycol 107-21-1 251 PPM DEVELOPMENTAL

Massachusetts Right To Know List:

Glycerin56-81-51 to 5 %2-Butoxyethanol111-76-21 to 5 %Triethanolamine102-71-61 to 5 %

New Jersey Right To Know List:

Glycerin 56-81-5 1 to 5 %

SDS for: SEALTITE PRO CLOSED CELL REGULAR

2-Butoxyethanol 111-76-2 1 to 5 % Triethanolamine 102-71-6 1 to 5 %

Pennsylvania Right To Know List:

Glycerin 56-81-5 1 to 5 % 2-Butoxyethanol 111-76-2 1 to 5 % Triethanolamine 102-71-6 1 to 5 % Diethylene glycol 111-46-6 5 to 10 %

SARA 302 Extremely Hazardous Substances:

- None

Chemicals subject to SARA 313 Reporting:

2-Butoxyethanol 111-76-2 1 to 5 % Emissions

Country Canada US Regulation Canada DSL Toxic Substances Control Act <u>All Components Listed</u> Yes Yes

16. Other Information:

Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Carlisle Spray Foam Insulation. The data on these sheets relates only to the specific material designated herein. Carlisle Spray Foam Insulation assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws.

Date revised: 2022-12-15 Date Prepared: 12/15/2022 **Reviewer Revision 2**