

Carlisle Spray Foam Insulation Safety Data Sheet

1. Identification of Substance:

Product Name: SEALTITE PRO OCX

Supplier Identification:Carlisle Spray Foam Insulation

Address:

100 Enterprise Dr. Cartersville, GA 30120 **Telephone:** (770) 607-0755

24-Hr. Emergency Phone Number:

CHEMTREC (800) 424-9300

INTERNATIONAL: +1-(703) 527-3887

Product Use: Polyurethane polyol component

2. Hazards Identification:

GHS Ratings:

Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Aquatic toxicity	C3	Acute toxicity > 10.0 but <= 100.0 mg/l and lack of rapid degradability and log Kow >= 4 unless BCF < 500 and unless chronic toxicity > 1 mg/l

GHS Hazards

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H412	Harmful to aquatic life with long lasting effects

GHS Precautions

P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash hands thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P272	Contaminated work clothing should not be allowed out of the workplace
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P310	Immediately call a POISON CENTER in case of overexposure.
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Specific treatment is urgent (see Section 4 First Aid measures)
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water

SDS for: SEALTITE PRO OCX

Page 1 of 7

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

IF IN EYES: Rinse continuously with water for several minutes. Remove contact P305+P351+P338

lenses if present and easy to do - continue rinsing

If skin irritation occurs: Get medical advice/attention P332+P313

If skin irritation or a rash occurs: Get medical advice/attention P333+P313

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents/container in accordance with existing federal, state, and local

environmental control laws.

Signal Word: Danger



Acute Toxicity:

Eyes: Corrosive to eyes. Skin: Irritating to skin.

Inhalation: Not expected to be a route of exposure. Ingestion: Harmful if swallowed. Consult physician.

Chronic Effects: Possible harmful target organ effects

3. Composition/Data on Components:

Chemical Name	CAS number	Weight Concentration %
Sucrose	57-50-1	20.00% - 30.00%
2-Propanol, 1-chloro-, phosphate (3:1)	13674-84-5	10.00% - 20.00%
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)omegahydroxy-, branched	127087-87-0	10.00% - 20.00%
Ethanol, 2-[[2-(dimethylamino)ethyl]methylamino]-	2212-32-0	1.00% - 5.00%
Dimethylaminoethoxyethanol	1704-62-7	1.00% - 5.00%
1,4-Dioxane	123-91-1	0.00% - 0.10%

4. First Aid Measures:

Inhalation: If inhaled and symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

After Eye Contact: Rinse opened eye for at least 15 minutes under running water. Remove contact lenses if present and easy to do so, and continue rinsing. If irritation persists contact physician

After Skin Contact: Clean affected area with soap and plenty of water.

SDS for: SEALTITE PRO OCX Page 2 of 7

Printed: 7/25/2019 at 11:54:25AM

After Swallowing: Consult physician.

Notes to Physician: Treat symptomatically.

5. Fire Fighting Measures:

Flash Point: >200°F, 93°C

LEL: N/A UEL: N/A

Upper and Lower Explosive Limits listed if known.

Suitable Extinguishing Agents: Water spray, CO2, Foam, Dry chemical.

Information about Protection against Explosions and Fires: Keep away from flames and sources of heat. Closed containers may rupture when exposed to extreme heat.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, oxides of phosphorus, hydrocarbons, traces of HCN, hydrogen chloride gas.

Protective Equipment: Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

6. Accidental Release Measures:

Person-Related Safety Precautions: Use appropriate personal protective equipment during clean up. Evacuate and keep unnecessary people out of spill area. Avoid contact with skin and eyes.

Measures for Environmental Protection: Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece) clean surface thoroughly to remove residual contamination.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

7. Handling and Storage:

Information for Safe Handling: Avoid contact with eyes, skin, or inhalation.

Storage Requirements: Store in dry, well ventilated area. Keep containers tightly closed. Store between 50°F-80°F. Material may settle.

Regulatory Requirements: Obey all local, state, and federal requirements.

SDS for: SEALTITE PRO OCX Page 3 of 7

8. Exposure Controls and Personal Protection:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sucrose 57-50-1	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	Not Established	Not Established	Not Established
Poly(oxy-1,2-ethanediyl), .alpha(4-nonylphenyl)ome gahydroxy-, branched 127087-87-0	Not Established	Not Established	Not Established
Ethanol, 2-[[2-(dimethylamino)ethyl]me thylamino]- 2212-32-0	Not Established	Not Established	Not Established
Dimethylaminoethoxyethanol 1704-62-7	Not Established	Not Established	Not Established
1,4-Dioxane 123-91-1	100 ppm TWA	20 ppm TWA	Not Established

Engineering Controls: No specific measures required if proper PPE precautions are followed.

General Protective and Hygienic Measures: Usual precautionary measures should be adhered to when handling chemicals.

Respiratory Protection: In spray applications, an organic vapor/particulate respirator or air supplied unit is necessary.

Protection of Hands: Protective chemical resistant gloves. **Eye Protection:** Chemical resistant goggles must be worn. **Body Protection:** Protective work clothing. Launder separately.

Contaminated Gear: Observe local requirements. Dispose of in accordance with local/state/federal regulations.

9. Physical and Chemical Properties:

Physical properties listed where known.

Appearance: Amber liquid	Odor: Amine odor	
Vapor Pressure: N/A	Odor threshold: N/A	
Vapor Density: N/A	pH: N/A	
Specific Gravity 1.20	Melting point: N/A	
Freezing point: N/A	Solubility: N/A	
Boiling range: 100 - 342°C	Flash point: >200°F,93°C	
Evaporation rate: N/A	Flammability: N/A	
Explosive Limits: N/A	Partition coefficient N/A (n-octanol/water):	
Autoignition temperature: N/A	Decomposition temperature: N/A	

SDS for: SEALTITE PRO OCX

Page 4 of 7

10. Stability and Reactivity:

Chemical Incompatible Materials: Avoid contact with isocyanates and strong oxidizing agents.

Hazardous Polymerization: Not expected to occur.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, oxides of phosphorus, hydrocarbons, traces of HCN, hydrogen chloride gas.

11. Toxicological Information:

Mixture Toxicity

Oral Toxicity LD50: 2,278mg/kg Dermal Toxicity LD50: 3,931mg/kg Inhalation Toxicity LC50: 27mg/L

Component Toxicity

13674-84-5 2-Propanol, 1-chloro-, phosphate (3:1)

Oral LD50: 500 mg/kg (Rat) Dermal LD50: 1,230 mg/kg (Rabbit) Inhalation LC50: 5 mg/L (Rat)

127087-87-0 Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched

Oral LD50: 1,310 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit)

2212-32-0 Ethanol, 2-[[2-(dimethylamino)ethyl]methylamino]-

Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit) Inhalation LC50: 20 mg/L (Rat

1704-62-7 Dimethylaminoethoxyethanol

Oral LD50: 2,460 mg/kg (Rat) Dermal LD50: 1,410 mg/kg (Rabbit)

123-91-1 1.4-Dioxane

Oral LD50: 4,200 mg/kg (Rat) Inhalation LC50: 49 mg/L (Rat)

Individual Toxicity Values Listed if Known

Acute Toxicity:

Eyes: Corrosive to eyes. **Skin:** Irritating to skin.

Inhalation: Not expected to be a route of exposure. **Ingestion:** Harmful if swallowed. Consult physician.

Chronic Effects: Possible harmful target organ effects.

Routes of Entry: Ingestion, skin contact, eye contact. Target Organs: Skin, eyes, reproductive system, kidneys **Chemicals with Known or Possible Carcinogenic Effects:**

% Weight Carcinogen Rating CAS Number Description

0.0 to 0.1% 1.4-Dioxane 1,4-Dioxane: IARC group 2B -123-91-1 Possibly carcinogenic to humans

12. Ecological Information:

General Information: Based on experience, no adverse effects are to be expected if correct disposal

SDS for: SEALTITE PRO OCX Page 5 of 7 Printed: 7/25/2019 at 11:54:25AM procedures have been followed as indicated in section 13.

Individual component ecotoxicity listed if known.

Component Ecotoxicity

2-Propanol, 1-chloro-, phosphate

(3:1)

96 Hr LC50 Brachydanio rerio: 56.2 mg/L [static]; 96 Hr LC50 Pimephales promelas:

98 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30 mg/L [static]

48 Hr EC50 Daphnia magna: 63 mg/L

72 Hr EC50 Desmodesmus subspicatus: 45 mg/L; 96 Hr EC50 Pseudokirchneriella

subcapitata: 4 mg/L

Poly(oxy-1,2-ethanediyl),

.alpha.-(4-nonylphenyl)-.omega.-hy

48 Hr LC50 Pimephales pormelas (fathead minnow): 3.8 - 6.2 mg/L 48 Hr EC50 Daphnia magna: 9.3 - 21.4 mg/L

droxy-, branched

16 Hr IC50 Bacteria: >1,000 mg/L

13. Disposal Considerations:

Recommendation: Observe local requirements. Dispose of in accordance with local/state/federal regulations.

Empty Container Precautions: Recondition or dispose of empty container in accordance with governmental regulations. If container is to be disposed, ensure all product residues are removed and container is empty prior to disposal.

14. Transport Information:

DOT Regulated Components:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods unless specifically cited below:

Agency Proper Shipping Name

<u>UN Number</u>

Packing Group Hazard Class

None

15. Regulatory Information:

OSHA HAZARD COMMUNICATION STANDARD: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA 311/312 Hazard Categories: Acute health hazard, chronic health hazard.

WARNING: This product can expose you to chemicals listed below, which are known to the State of California to cause cancer, birth defects, or reproductive harm. For more information, visit www.P65Warnings.ca.gov

Ethylene Oxide 75-21-8 1 PPM CARC 1,4-Dioxane 123-91-1 3 PPM CARC

Massachusetts Right To Know List:

Sucrose 57-50-1 20 to 30 %

New Jersey Right To Know List:

Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched 127087-87-0 10 to 20 %

Pennsylvania Right To Know List:

SDS for: SEALTITE PRO OCX

Page 6 of 7

Printed: 7/25/2019 at 11:54:25AM

Sucrose 57-50-1 20 to 30 %

Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched 127087-87-0 10 to 20 %

SARA 302 Extremely Hazardous Substances:

- None

Chemicals subject to SARA 313 Reporting:

Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched 127087-87-0 10 to 20 % Emissions

<u>Country</u> <u>Regulation</u> <u>All Components Listed</u>

Canada DSL Yes
US Toxic Substances Control Act Yes

16. Other Information:

Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Carlisle Spray Foam Insulation. The data on these sheets relates only to the specific material designated herein. Carlisle Spray Foam Insulation assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws.

Date revised: 7/25/2019 Reviewer Revision 1

Date Prepared: 7/25/2019

SDS for: SEALTITE PRO OCX

Page 7 of 7

Printed: 7/25/2019 at 11:54:25AM